



Description: XEL-T8-20WD is a high-efficiency LED lights, compatible with TRIAC dimmer, Environmental water plating chromium of Plug , Look beautiful , no additional support, easy to install.

	<p>Features:</p> <ol style="list-style-type: none"> 1. High light efficiency, saving 50% than the fluorescent tubes 2. Environmental water plating chromium of Plug, With screws, easy to install 3. TRIAC dimmer compatible , Dimming consistency, and flicker-free 4. Diffusion-PC tube, light uniformity, notbroken 5. No highlights, no flicker, no harmful rays (UV-IR), Green, no mercury 6. Long life, more than 40,000 hours <p>Scope of application: Display cabinets, showcase, underground garage Replacement of fluorescent tubes</p>
	<p>Mechanical Specifications: Main Material: LED, aluminum PCB, PC tube,Epoxy Environmental water plating chromium of Plug Dimensions: See below Diameter 26mm T8 Optional length :60cm, 90cm, 120cm Operating Temperature: -20°C~55°C Weight: 450g (120cm) IP Grade: IP65</p> <p>Electronical Specifications: Input Voltage:AC100 ,AC230V Output Brightness: 80Lm/W Color index: Ra 80</p>

XEL-T8-20WD Data Sheet

MODEL	Length mm	power	Input	Luminous flux	Illuminance Lux Spacing1m	Application scope	Features
XEL-T8-20WD	1200	20W	AC100, AC230V	1600Lm	290Lx	Cabinets, display cases, showcase,Underground car park lighting,Substitute the same size of fluorescent tubes, energy-saving 50%	TRIAC dimmer compatible with built-in power
	900	14W		1120Lm	235Lx		
	600	7.5W		600Lm	175Lx		

Note:
The above figures: white LED color temperature 6000-7000K, the test temperature is 25 °C, the input voltage AC230V, Please note that connection to install protective wire
Learn dimmer compatible models, Dimmer phase relationship with the current ,please contact us

